

MORE INFO >>

		P	CCT	I	Flux	LOR
<b>SWAP M</b> CRI>90	A212-21-10-   W   R   G   Z   WN   N   W65	5W	2700K	150mA	675 lm	86%
	A212-21-11-   W   R   G   Z   WN   N   W65	5W	3000K	150mA	700 lm	86%
	A212-21-12-   W   R   G   Z   WN   N   W65	5W	4000K	150mA	710 lm	86%
	A212-22-10-   W   R   G   Z   WN   N   W65	7W	2700K	200mA	910 lm	86%
	A212-22-11-   W   R   G   Z   WN   N   W65	7W	3000K	200mA	940 lm	86%
	A212-22-12-   W   R   G   Z   WN   N   W65	7W	4000K	200mA	960 lm	86%
	A212-22-20-   W   R   G   Z   WN   N   W65	7W	2700K	200mA	910 lm	86%
	A212-22-21-   W   R   G   Z   WN   N   W65	7W	3000K	200mA	940 lm	86%
	PHASE CUT** A212-22-22-   W   R   G   Z   WN   N   W65	7W	4000K	200mA	960 lm	86%
	A212-22-30-   W   R   G   Z   WN   N   W65	7W	2700K	200mA	910 lm	86%
	A212-22-31-   W   R   G   Z   WN   N   W65	7W	3000K	200mA	940 lm	86%
	DALI   PUSH** A212-22-32-   W   R   G   Z   WN   N   W65	7W	4000K	200mA	960 lm	86%
<b>SWAP M</b> <b>Super CRI</b> CRI>97	A312-22-10-   W   R   G   Z   WN   N   W65	7W	2700K	200mA	770 lm	86%
	A312-22-11-   W   R   G   Z   WN   N   W65	7W	3000K	200mA	800 lm	86%
	A312-22-12-   W   R   G   Z   WN   N   W65	7W	4000K	200mA	820 lm	86%
	A312-22-20-   W   R   G   Z   WN   N   W65	7W	2700K	200mA	770 lm	86%
	A312-22-21-   W   R   G   Z   WN   N   W65	7W	3000K	200mA	800 lm	86%
	PHASE CUT** A312-22-22-   W   R   G   Z   WN   N   W65	7W	4000K	200mA	820 lm	86%
	A312-22-30-   W   R   G   Z   WN   N   W65	7W	2700K	200mA	770 lm	86%
	A312-22-31-   W   R   G   Z   WN   N   W65	7W	3000K	200mA	800 lm	86%
	DALI   PUSH** A312-22-32-   W   R   G   Z   WN   N   W65	7W	4000K	200mA	820 lm	86%

220-240 V~ | IP20 | IP65\* | L90B10 >55.000h




		P	CCT	I	Flux	LOR
<b>SWAP M</b> <b>DIM to warm</b> CRI>90	PHASE CUT** A212-23-29-   W   R   G   Z   WN   N   W65	6W	3000-1800K	350mA	640 lm	80%
	DALI   PUSH** A212-23-39-   W   R   G   Z   WN   N   W65	6W	3000-1800K	350mA	640 lm	80%

220-240 V~ | IP20 | IP65\* | L80B10 >55.000h



OPTIONAL ACCESSORIES



\*SWAP IP65

AFFECTS THE LIGHTING PARAMETERS

WHITE - DIRECT REFERENCE	LOR
W65 <input type="checkbox"/>	81%
W65 <input type="checkbox"/> DIM TO WARM	76%

OTHER COLOURS

REFERENCE + A212-20-65- | W | N | IP65 ACCESSORY M

PRE-ASSEMBLED. NOT SOLD SEPARATELY



FLAT SPRING ACCESSORY

A212-00-00

ACCESSORY FOR CONCRETE CEILINGS. NOT PRE-ASSEMBLED. SELF-INSTALLATION KIT TOGETHER WITH THE PRODUCT.



↑↑↑ \*IP65



COLOUR | W  | R  | G  | Z  | WN  | N  | MATERIAL | AL  | PC  | PC  | RAL  » 312

\*\* OTHER DIM OPTIONS PLEASE CONSULT | COLOURS MAY AFFECT THE LIGHTING PARAMETERS

» 288