

MORE INFO >>

		P	CCT	I	Flux	LOR
SHOT LIGHT M 1 Trimless	A298-01-10- N W NMG	5W	2700K	150mA	675 lm	86%
	A298-01-11- N W NMG	5W	3000K	150mA	700 lm	86%
	A298-01-12- N W NMG	5W	4000K	150mA	710 lm	86%
SHOT LIGHT M 2 Trimless	A298-02-10- N W NMG	6,5W	2700K	200mA	910 lm	86%
	A298-02-11- N W NMG	6,5W	3000K	200mA	940 lm	86%
	A298-02-12- N W NMG	6,5W	4000K	200mA	960 lm	86%
	A298-02-30- N W NMG	6,5W	2700K	200mA	910 lm	86%
	A298-02-31- N W NMG	6,5W	3000K	200mA	940 lm	86%
	DALI PUSH* A298-02-32- N W NMG	6,5W	4000K	200mA	960 lm	86%
SHOT LIGHT M 3 Trimless	A298-03-10- N W NMG	10,3W	2700K	300mA	1230 lm	86%
	A298-03-11- N W NMG	10,3W	3000K	300mA	1280 lm	86%
	A298-03-12- N W NMG	10,3W	4000K	300mA	1300 lm	86%
	A298-03-30- N W NMG	10,3W	2700K	300mA	1230 lm	86%
	A298-03-31- N W NMG	10,3W	3000K	300mA	1280 lm	86%
DALI PUSH* A298-03-32- N W NMG	10,3W	4000K	300mA	1300 lm	86%	

220-240 V~ | IP20 | CRI>90 | L90B10 > 55.000h




* DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT



ACCESSORY

SHOT LIGHT M Trimless Accessory** A298-00-00

** MANDATORY FOR INSTALLATION





OPTIONAL ACCESSORIES

SHOT LIGHT M High Chromatic LED ⓘ >> 281

NOT SOLD SEPARATELY | AFFECTS THE LIGHTING PARAMETERS

TRIMLESS TOOL D79 X D120mm A478-00-05



COLOUR | N ■ | W □ | NMG ■■ |

MATERIAL | AL | ABS+PC |

RAL ⓘ >> 312

COLOURS MAY AFFECT THE LIGHTING PARAMETERS
"THE INVISIBLE BLACK" IS ONLY AVAILABLE FOR N & NMG COLOURS

Ⓢ & ⓘ >> 288