



SHOT LIGHT



MORE INFO >>


	P	CCT	Beam	I	Flux	LOR
SHOT LIGHT	A268-01-10- N NMG WMG	2,1W	2700K	19°	700mA	190 lm 90%
	A268-01-11- N NMG WMG	2,1W	3000K	19°	700mA	210 lm 90%
	A268-01-12- N NMG WMG	2,1W	4000K	19°	700mA	250 lm 90%
	A268-01-20- N NMG WMG	2,1W	2700K	38°	700mA	190 lm 92%
	A268-01-21- N NMG WMG	2,1W	3000K	38°	700mA	210 lm 92%
	A268-01-22- N NMG WMG	2,1W	4000K	38°	700mA	250 lm 92%

220
240 V~ | IP20 | CRI>90 | L90B10
>102.000h



EASY INSTALLATION

DRIVER FITS INTO
CUT-OUT DIAMETER



COLOUR | N ■ | NMG ■■ | WMG □□

MATERIAL | AL | ABS+PC


RAL > 312

* DIM OPTIONS PLEASE CONSULT

& > 288




Extended Family
Shot Light Surface_P.110



MORE INFO >>


		P	CCT	Beam	I	Flux	LOR
SHOT LIGHT IP65	A268-02-20- N W NMG WMG	2,1W	2700K	38°	700mA	190 lm	86%
	A268-02-21- N W NMG WMG	2,1W	3000K	38°	700mA	210 lm	86%
	A268-02-22- N W NMG WMG	2,1W	4000K	38°	700mA	250 lm	86%

220
240 V~ | IP65 | CRI>90 | L90B10 > 102.000h



EASY INSTALLATION

DRIVER FITS INTO
CUT-OUT DIAMETER



COLOUR | N ■ | W □ | NMG ■■ | WMG □□ |

MATERIAL | AL | ABS+PC |

RAL » 312

* DIM OPTIONS PLEASE CONSULT | "THE INVISIBLE BLACK" IS ONLY AVAILABLE FOR N, NMG & WMG COLOURS

& » 288