


# SWAP



MORE INFO >>

		P	CCT	I	Flux	LOR
<b>SWAP S</b> CRI>90	A212-11-10-   W   R   G   Z   WN   N   W65	5W	2700K	150mA	675 lm	86%
	A212-11-11-   W   R   G   Z   WN   N   W65	5W	3000K	150mA	700 lm	86%
	A212-11-12-   W   R   G   Z   WN   N   W65	5W	4000K	150mA	710 lm	86%
	A212-12-10-   W   R   G   Z   WN   N   W65	7W	2700K	200mA	910 lm	86%
	A212-12-11-   W   R   G   Z   WN   N   W65	7W	3000K	200mA	940 lm	86%
	A212-12-12-   W   R   G   Z   WN   N   W65	7W	4000K	200mA	960 lm	86%
	A212-12-20-   W   R   G   Z   WN   N   W65	7W	2700K	200mA	910 lm	86%
	A212-12-21-   W   R   G   Z   WN   N   W65	7W	3000K	200mA	940 lm	86%
	PHASE CUT** A212-12-22-   W   R   G   Z   WN   N   W65	7W	4000K	200mA	960 lm	86%
	A212-12-30-   W   R   G   Z   WN   N   W65	7W	2700K	200mA	910 lm	86%
	A212-12-31-   W   R   G   Z   WN   N   W65	7W	3000K	200mA	940 lm	86%
	DALI I PUSH** A212-12-32-   W   R   G   Z   WN   N   W65	7W	4000K	200mA	960 lm	86%
<b>SWAP S</b> Super CRI CRI>97	A312-12-10-   W   R   G   Z   WN   N   W65	7W	2700K	200mA	770 lm	86%
	A312-12-11-   W   R   G   Z   WN   N   W65	7W	3000K	200mA	800 lm	86%
	A312-12-12-   W   R   G   Z   WN   N   W65	7W	4000K	200mA	820 lm	86%
	A312-12-20-   W   R   G   Z   WN   N   W65	7W	2700K	200mA	770 lm	86%
	A312-12-21-   W   R   G   Z   WN   N   W65	7W	3000K	200mA	800 lm	86%
	PHASE CUT** A312-12-22-   W   R   G   Z   WN   N   W65	7W	4000K	200mA	820 lm	86%
	A312-12-30-   W   R   G   Z   WN   N   W65	7W	2700K	200mA	770 lm	86%
	A312-12-31-   W   R   G   Z   WN   N   W65	7W	3000K	200mA	800 lm	86%
	DALI I PUSH** A312-12-32-   W   R   G   Z   WN   N   W65	7W	4000K	200mA	820 lm	86%

220 240 V~ | IP20 | IP65\* | L90B10 >55.000 h



		P	CCT	I	Flux	LOR
<b>SWAP S</b> DIM to warm CRI>90	PHASE CUT** A212-13-29-   W   R   G   Z   WN   N   W65	6W	3000-1800K	350mA	640 lm	80%
	DALI I PUSH** A212-13-39-   W   R   G   Z   WN   N   W65	6W	3000-1800K	350mA	640 lm	80%

220 240 V~ | IP20 | IP65\* | L80B10 >55.000 h



## OPTIONAL ACCESSORY

### \*SWAP IP65



AFFECTS THE LIGHTING PARAMETERS

WHITE · DIRECT REFERENCE	LOR
W65 <input type="checkbox"/>	81%
W65 <input type="checkbox"/> DIM TO WARM	76%

### OTHER COLOURS

REFERENCE + A212-10-65- | W | N |

PRE-ASSEMBLED. NOT SOLD SEPARATELY



COLOUR |  W |  R |  G |  Z |  WN |  N | MATERIAL |  AL |  PC |  PC | RAL >> 132

\*\* OTHER DIM OPTIONS PLEASE CONSULT | COLOURS MAY AFFECT THE LIGHTING PARAMETERS

& >> 288