



SLIM



Housing
Matt natural anodized, aluminum extrusion profile and stainless steel mounting accessories with plastic ceiling cup.

Optics
Opal, white, diffusing polycarbonate lens with lambertian light distribution.

Led
High-efficacy mid power LED with CRI > 80, achieving L90B50 ≥ 50,000 hours of lifetime

Driver
Constant current output LED driver with high efficiency and Pf≥0.95

Operating Temperature Range
0 °C/+35 °C

Options
Dimming via DALI

Color
Matte natural anodized

LL Low Lumen
HL High Lumen

| Type Code | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz | Weight (Kg) | L (mm) | Lumen Variations |
|-----------------|-----------|---------|-------------------|-----|---------------|-------------|--------|------------------|
| SSIM.0860.33.30 | 33 | 3000 | 2900 | >80 | 220-240/50-60 | 1,6 | 860 | HL |
| SSIM.0860.33.40 | 33 | 4000 | 3080 | >80 | 220-240/50-60 | 1,6 | 860 | HL |
| SSIM.0860.23.30 | 23 | 3000 | 1970 | >80 | 220-240/50-60 | 1,6 | 860 | LL |
| SSIM.0860.23.40 | 23 | 4000 | 2100 | >80 | 220-240/50-60 | 1,6 | 860 | LL |
| SSIM.1140.44.30 | 44 | 3000 | 3970 | >80 | 220-240/50-60 | 2 | 1140 | HL |
| SSIM.1140.44.40 | 44 | 4000 | 4230 | >80 | 220-240/50-60 | 2 | 1140 | HL |
| SSIM.1140.30.30 | 30 | 3000 | 2850 | >80 | 220-240/50-60 | 2 | 1140 | LL |
| SSIM1140.30.40 | 30 | 4000 | 3030 | >80 | 220-240/50-60 | 2 | 1140 | LL |
| SSIM.1420.54.30 | 54 | 3000 | 4680 | >80 | 220-240/50-60 | 2,3 | 1420 | HL |
| SSIM.1420.54.40 | 54 | 4000 | 4980 | >80 | 220-240/50-60 | 2,3 | 1420 | HL |
| SSIM.1420.38.30 | 38 | 3000 | 3250 | >80 | 220-240/50-60 | 2,3 | 1420 | LL |
| SSIM.1420.38.40 | 38 | 4000 | 3430 | >80 | 220-240/50-60 | 2,3 | 1420 | LL |
| SSIM.1700.65.30 | 65 | 3000 | 5970 | >80 | 220-240/50-60 | 2,65 | 1700 | HL |

| Type Code | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz | Weight (Kg) | L (mm) | Lumen Variations |
|------------------|-----------|---------|-------------------|-----|---------------|-------------|--------|------------------|
| SSIM.1700.65.40 | 65 | 4000 | 6310 | >80 | 220-240/50-60 | 2,65 | 1700 | HL |
| SSIM.1700.46.30 | 46 | 3000 | 4380 | >80 | 220-240/50-60 | 2,65 | 1700 | LL |
| SSIM.1700.46.40 | 46 | 4000 | 4630 | >80 | 220-240/50-60 | 2,65 | 1700 | LL |
| SSIM.1980.76.30 | 76 | 3000 | 7000 | >80 | 220-240/50-60 | 3 | 1980 | HL |
| SSIM.1980.76.40 | 76 | 4000 | 7450 | >80 | 220-240/50-60 | 3 | 1980 | HL |
| SSIM.1980.53.30 | 53 | 3000 | 5130 | >80 | 220-240/50-60 | 3 | 1980 | LL |
| SSIM.1980.53.40 | 53 | 4000 | 5410 | >80 | 220-240/50-60 | 3 | 1980 | LL |
| SSIM.2260.87.30 | 87 | 3000 | 8080 | >80 | 220-240/50-60 | 3,6 | 2260 | HL |
| SSIM.2260.87.40 | 87 | 4000 | 8450 | >80 | 220-240/50-60 | 3,6 | 2260 | HL |
| SSIM.2260.61.30 | 61 | 3000 | 5920 | >80 | 220-240/50-60 | 3,6 | 2260 | LL |
| SSIM.2260.61.40 | 61 | 4000 | 6220 | >80 | 220-240/50-60 | 3,6 | 2260 | LL |
| SSIM.2540.98.30 | 98 | 3000 | 9290 | >80 | 220-240/50-60 | 3,9 | 2540 | HL |
| SSIM.2540.98.40 | 98 | 4000 | 9890 | >80 | 220-240/50-60 | 3,9 | 2540 | HL |
| SSIM.2540.68.30 | 68 | 3000 | 6620 | >80 | 220-240/50-60 | 3,9 | 2540 | LL |
| SSIM.2540.68.40 | 68 | 4000 | 7050 | >80 | 220-240/50-60 | 3,9 | 2540 | LL |
| SSIM.2820.109.30 | 109 | 3000 | 9940 | >80 | 220-240/50-60 | 4,25 | 2820 | HL |
| SSIM.2820.109.40 | 109 | 4000 | 10580 | >80 | 220-240/50-60 | 4,25 | 2820 | HL |
| SSIM.2820.76.30 | 76 | 3000 | 7310 | >80 | 220-240/50-60 | 4,25 | 2820 | LL |
| SSIM.2820.76.40 | 76 | 4000 | 7780 | >80 | 220-240/50-60 | 4,25 | 2820 | LL |

