



# FIT 65 1L

Magnetic 24V Fit\_P.92  
Fit Recessed\_P.100

Fit Surface\_P.124  
Fit 24V\_P.184  
Fit 48V\_P.197

Extended Family  
Fit\_P.228  
Black Foster Fit 35\_P.246  
Black Foster Fit 27\_P.249




MORE INFO >>

		P	CCT	Beam	I	Flux	LOR
FIT 65 1L	A366-01-11-   WT   NT	10,3W	3000K	18°	300mA	1300 lm	90%
	A366-01-12-   WT   NT	10,3W	4000K	18°	300mA	1320 lm	90%
	A366-01-21-   WT   NT	10,3W	3000K	26°	300mA	1300 lm	88%
	A366-01-22-   WT   NT	10,3W	4000K	26°	300mA	1320 lm	88%
	A366-01-31-   WT   NT	10,3W	3000K	36°	300mA	1300 lm	84%
	A366-01-32-   WT   NT	10,3W	4000K	36°	300mA	1320 lm	84%

220  
240 V~ | IP20 | CRI>90 | L90B10 >55.000h



TRACK LIGHTS



VISIBLE LIMIT

### OPTIONAL ACCESSORY

**FIT 65 Anti-glare Honeycomb Louver** A356-00-00

NOT SOLD SEPARATELY  
AFFECTS THE LIGHTING PARAMETERS



COLOUR | WT  | NT

MATERIAL | AL | OPTICAL PMMA |

TRACK 1L » 218

COLOUR | WT  | NT

MATERIAL | AL | PC |