

Fixture Specifications

Protection . IP 66 - IK 08

Body . Anticorodal turning aluminum 6000 Serie,
for greater corrosion resistance

Frame . Steel AISI 316L


Screen . Extra-clear transparent Glass 6mm

Seals . EPDM rubber

Screws . Stainless steel A2

Paint / Finishing . Anti-corrosive UV stabilised
polyester powder

Finishes




00
PURE WHITE
RAL 9016




10
WHITE
RAL 9010



24
BRONZE




25
RUST



01
BLACK
RAL 9005




30
ANTHRACITE



35
SLATE GREY



40
GREY
RAL 9006



55
GREEN COOL
MINT
RAL 6019

New Color

Technical Data

NB FASCIO STRETTO 15° - NARROW BEAM 15°

MB FASCIO MEDIO 30° - MEDIUM BEAM 30°

WB FASCIO LARGO 40° - WIDE BEAM 40°


2700K - 3000K - 4000K

Versione in Tensione - Constant voltage (Vdc)

2W con DRIVER REMOTO 24Vdc - 2W REMOTE DRIVER 24Vdc

Versione in Corrente - Constant current (mA)

2W con DRIVER REMOTO MAX 700mA - 2W REMOTE DRIVER max 700mA



Quote espresse in millimetri "mm"
Share expressed in millimeters "mm"

Sizes . H65 x L46 x W58

Specifications



BLOOM MINI

led WHITE

Versione in Tensione - Constant voltage (Vdc)


LED SYSTEM WITH REMOTE DRIVER 24V

code	beam	class	power	W	source	fixture	CCT LED	CRI
5000W /HRRCNB	 NB Spot/15°	III	24Vdc	2W	170 lm	130 lm	2700K	80
5000W /WRRCNB	 NB Spot/15°	III	24Vdc	2W	170 lm	130 lm	3000K	80
5000W /NRRCNB	 NB Spot/15°	III	24Vdc	2W	190 lm	150 lm	4000K	80
5000W /HRRCMB	 MB Flood/30°	III	24Vdc	2W	170 lm	125 lm	2700K	80
5000W /WRRCMB	 MB Flood/30°	III	24Vdc	2W	170 lm	125 lm	3000K	80
5000W /NRRCMB	 MB Flood/30°	III	24Vdc	2W	190 lm	145 lm	4000K	80
5000W /HRRCWB	 WB Wide Flood/40°	III	24Vdc	2W	170 lm	120 lm	2700K	80
5000W /WRRCWB	 WB Wide Flood/40°	III	24Vdc	2W	170 lm	120 lm	3000K	80
5000W /NRRCWB	 WB Wide Flood/40°	III	24Vdc	2W	190 lm	140 lm	4000K	80

Versione in Corrente - Constant current (mA)

LED SYSTEM WITH REMOTE DRIVER max 700mA

code	beam	class	power	W	source	fixture	CCT LED	CRI
5000W /HRCCNB	 NB Spot/15°	III	700mA	2W	220 lm	170 lm	2700K	80
5000W /WRCCNB	 NB Spot/15°	III	700mA	2W	220 lm	170 lm	3000K	80
5000W /NRCCNB	 NB Spot/14°	III	700mA	2W	240 lm	188 lm	4000K	80
5000W /HRCCMB	 MB Flood/30°	III	700mA	2W	220 lm	165 lm	2700K	80
5000W /WRCCMB	 MB Flood/30°	III	700mA	2W	220 lm	165 lm	3000K	80
5000W /NRCCMB	 MB Flood/30°	III	700mA	2W	240 lm	183 lm	4000K	80
5000W /HRCCWB	 WB Wide Flood/40°	III	700mA	2W	220 lm	162 lm	2700K	80
5000W /WRCCWB	 WB Wide Flood/40°	III	700mA	2W	220 lm	162 lm	3000K	80
5000W /NRCCWB	 WB Wide Flood/40°	III	700mA	2W	240 lm	180 lm	4000K	80



Accessories



informazioni sugli accessori a pag. xxx e sul nostro sito web
information about accessories at page xxx and on our website

SPIKE

BELT

DRIVER 24Vdc / mA

HUB for electronic parts



Specifications



website-link

BLOOM **MINI** light diffusion

NB



FASCIO STRETTO 14° - NARROW BEAM 14°

MB



FASCIO MEDIO 30° - MEDIUM BEAM 30°

WB



FASCIO LARGO 40° - WIDE BEAM 40°

Luminaire installation example:
Installation height: 4mt
Distance between luminaires: 4mt



Augenti[®]

13/bloom_mini FLOODLIGHT

BLOOM

BEAM

NB

MB

WB



Augenti

15/bloom_mini FLOODLIGHT